

# RevSpin RS- 102, 150, & 200

## Microcentrifuges



Revolutionary Science

Manufacturer of Precision Laboratory Equipment

The RevSpin Microcentrifuges are stronger, faster, and contain more than twice the capacity of competing pal-sized microcentrifuges. An oversized rubber base increases the reliability of the RevSpin models by absorbing vibration and limiting bench walking. Optional PCR rotors are available for all RevSpin units. Two year warranty included.

### RS -102 specification

|                     |   |
|---------------------|---|
| Capacity:           | 16 position rotor                             |
| Tube Size:          | 1.5 or 2.0mL                                  |
| Speed Selections:   | Off/Pulse/6,000RPM/10,000RPM                  |
| RPM:                | 6,000 (low), 10,000 (high)                    |
| RCF:                | 1,735/2,245 (low), 4,819/6,238 (high)         |
| Power Requirements: | 110-120 VAC, 60Hz, 1.5 A, grounded cord       |
| Display:            | Easy to use turn dial                         |
| Durability:         | 8mm oversized shaft                           |
| Safety:             | Power automatically shuts if when lid is ajar |



888.322.5722  
www.cplabsafety.com

E-mail: [info@cplabsafety.com](mailto:info@cplabsafety.com)  
Website: [www.calpaclab.com](http://www.calpaclab.com)

ISO 9001  
REGISTERED FIRM

# RevSpin RS- 102, 150, & 200

## Microcentrifuges



Revolutionary Science  
Manufacturer of Precision Laboratory Equipment

### RS -150 specifications

|                     |   |
|---------------------|---|
| Capacity:           | 16 position rotor                             |
| Tube Size:          | 1.5 or 2.0mL                                  |
| Speed Selections:   | Off/Pulse/6,000RPM/10,000RPM                  |
| RPM:                | 6,000 (low), 10,000 (high)                    |
| RCF:                | 1,735/2,245 (low), 4,819/6,238 (high)         |
| Power Requirements: | 110-230 VAC, 50 -60 Hz, 1.5 A, grounded cord  |
| Simplicity:         | Two button operation                          |
| Durability:         | 8mm oversized shaft                           |
| Safety:             | Power automatically shuts if when lid is ajar |



### RS -200 specifications

|                     |   |
|---------------------|---|
| Capacity:           | 16 position rotor                             |
| Tube Size:          | 1.5 or 2.0mL                                  |
| Speed Selections:   | Multiple speeds up to 10,000RPM               |
| RPM:                | 10,000 max                                    |
| RCF:                | 6,238 max                                     |
| Power Requirements: | 110-230 VAC, 50 -60 Hz, 1.5 A, grounded cord  |
| Timer:              | 60 minute digital timer                       |
| Simplicity:         | Easy to read digital display                  |
| Durability:         | 8mm oversized shaft                           |
| Safety:             | Power automatically shuts if when lid is ajar |



888.322.5722  
www.cplabsafety.com

E-mail: [info@cplabsafety.com](mailto:info@cplabsafety.com)  
Website: [www.calpaclab.com](http://www.calpaclab.com)

ISO 9001  
REGISTERED FIRM